

## Pull Out Disconnect Switches

### Applications:

Air conditioners	Refrigeration
Heat Pumps	Hot tubs
Mini-Split A/C systems	Swimming Pools
Lighting	Spas
Pumps	Miscellaneous



Part #	Type	Enclosure	Amps
W-PDS-N60	Non-Fusible	Metallic	60
W-PDS-F30	Fusible	Metallic	30
W-PDS-F60	Fusible	Metallic	60
*W-PDN-N60	Non-Fusible	Nonmetallic	60
*W-PDN-F30	Fusible	Nonmetallic	30
*W-PDN-F60	Fusible	Nonmetallic	60
*W-MBS-60	Circuit Breaker	Metallic	60
* future items			

### Specifications:

- UL and cUL LISTED Enclosed Pullout Switch E493757
- Intended for 208/240VAC Single Phase Circuits
- All copper contacts for use with copper wiring
- Multiple knockouts on all sides, slotted holes for easy wall mounting
- Puller may be stored inside the enclosure for non-fusible units
- Fusible switches accept Class H fuses (not included)
- NEMA 3R raintight enclosure, powder coated galvanized steel
- Tested successfully to more than 1000 hours of salt spray
- Dead front panel separating user from live components
- Removable cover with padlock tab
- \* Circuit Breaker type includes 2 pole UL-489 MCB